
### **Spec Sheet**

# SMD Power Inductors (NR series S type)

# NRS4018T221MDGJ



#### Features

- Item Summary 220uH±20%, 0.17A, 4.0x4.0x1.8mm
- Lifecycle Stage
   Mass Production
- Standard packaging quantity (minimum)
   Taping Embossed 3500pcs


#### ■ Products characteristics table

Inductance	220 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	0.17 A
Saturation Current (max)	0.275 A
Saturation Current (typ)	0.31 A
Temperature Rise Current (max)	0.17 A
Temperature Rise Current (typ)	0.21 A
DC Resistance (max)	4.56 Ω
DC Resistance (typ)	3.8 Ω
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	4 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 20 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

#### External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.8 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

### Recommended Land Patterns



2017.04.30

# SMD Power Inductors (NR series S type)

## NRS4018T221MDGJ

Dimension unit: mm unit: inch

Length: 4.0 +/- 0.2 (0.157 +/- 0.008)

Width: 4.0 +/- 0.2 (0.157 +/- 0.008)

Height: 1.8 max. (0.071 max.)



Inductance: 220 uH (test freq at 0.1MHz)
DC Resistance: 3.8 / 4.56 ohm (typ / max)

Saturation Current: 275 mA ( max ) Temp. rise Current: 170 mA ( max )

Saturation current typical: 30% reduction from initial L value.

Temp rise Current typical: Temperature will rise by 40 deg C

