


Multilayer Ceramic Devices (Band Pass Type)

FI212B245027-T



Unit:mm

■ Features

- Item Summary
Band Pass Type, 2.0x1.25x1.0mm
for Bluetooth/W-LAN/ZigBee
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping Embossed 3000

■ Products characteristics table

System	Bluetooth/W-LAN/ZigBee
Passband Frequency1 (f1)	2400 to 2500 MHz
Insertion Loss2 (max)(in f1)	1.7 dB at 2400 to 2500MHz (-30 to +85 °C)
Ripple1 (max)(in f1)	1 dB at 2400 to 2500MHz
VSWR1 (max)(in f1)	2 at 2400 to 2500MHz
Attenuation1 (min)(f1)	30 dB at 880 to 915MHz
Attenuation2 (min)(f1)	30 dB at 1710 to 1910MHz
Attenuation3 (min)(f1)	6 dB at 2110 to 2170MHz
Attenuation4 (min)(f1)	20 dB at 4800 to 5000MHz
Input Impedance	50 Ω
Output Impedance	50 Ω
Operating Temp. Range	-30 to +85 °C
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

■ External Dimensions

Dimension L	2.0 ± 0.15 mm
Dimension W	1.25 ± 0.15 mm
Dimension T	Max 1.0 mm

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.