

Product Overview

LB1948MC: Motor Driver, Forward / Reverse, Low Saturation Voltage, 12 V

For complete documentation, see the data sheet

The LB1948MC is a two-channel low saturation voltage forward/reverse motor driver IC. It is optimal for motor drive in 12V system products and can drive either two DC motors, one DC motor using parallel connection, or a two-phase bipolar stepping motor with 1-2 phase excitation mode drive.

Features

- 20 V max operating voltage
- Zero current drawn in standby mode
- Braking function
- Built-in spark killer diode
- Built-in thermal shutdown circuit
- Miniature package: MFP-10SK (6.2mm 5.0mm)
- Low saturation voltage: $V_{O(sat)} = 0.5V$ (typical) at $I_O = 400mA$
- Supports parallel connection: $I_O \text{ max} = 1.6A$, $V_{O(sat)} = 0.6V$ (typical) at $I_O = 800mA$

Applications

- Consumer
- Industrial

Benefits

- Good safety margin for driving 12V motors
- Saving energy
- Safety design
- Spark killer
- Thermal protection
- Small mounting space

End Products

- Refrigerator
- Thermal printers
- POS terminal
- Hot-water supplies
- Time Recorder

Part Electrical Specifications

Product	Compliance	Status	V_M Min (V)	V_M Max (V)	V_{CC} Min (V)	V_{CC} Max (V)	I_O Max (A)	I_O Peak Max (A)	Step Reso- lution	Contr- ol Type	Feed- back Meth- od	Curre- nt Sens- e	Regu- lator Outp- ut	Fault Dete- ction	Flyba- ck Prote- ction	$R_{DS(on)}$ Typ (Ω)	Pack- age Type
LB1948MC-AH	Pb-free Halide free	Active	2.5	16	2.5	16		0.8	1/2	Paral- lel		None		Ther- mal			SOIC- 10 W / MFP- 10SK

For more information please contact your local sales support at www.onsemi.com

Created on: 4/29/2017