
Spec Sheet

Multilayer Ceramic Capacitors for High Frequency Applications

UVK105CH4R3JW-F



Features

- Item Summary
- 50V, C0H, 4.3pF, ±5%, 0402
- Lifecycle Stage
- Mass Production
- Standard packaging quantity (minimum)
 Taping paper 10000pcs

Products characteristics table

| CaseSize (EIA/JIS) | 0402/1005 |
|---------------------------------------|---------------------------|
| Rated Voltage (max) | 50V |
| Capacitance | 4.3pF |
| Capacitance Tolerance | ±5% |
| Resistance | 10,000 MΩ min. |
| Q (min) | 84 |
| Temperature Characteristics (EIA/JIS) | С0Н/СН |
| Temperature Range (EIA/JIS) | -55 to +125℃/-55 to +125℃ |
| RoHS Compliance | Yes |
| Halogen Free | Yes |
| Soldering Method | Reflow |

External Dimensions

| L | 1.0mm ±0.05 |
|---|-------------|
| W | 0.5mm ±0.05 |
| т | 0.5mm ±0.05 |
| е | 0.25mm ±0.1 |

The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the Date at any time without notice. Before making final selection, please check product specification.