



NOTE: STRAP CANNOT COVER BANDING.

LEAD FINISH: SOLDER			
GROUND STRAP: FINISH: SILVER			
CAPACITANCE pF	12,000pF GMV		
TEMP. RANGE	-55°C TO 125°C		
CURRENT	10 AMP DC		
WORKING VOLTAGE	85°C, 100 VDC 125°C, 70 VDC		
D.C. RESISTANCE	.01 ohms		
INSERTION LOSS PER MIL-STD-2201 (NO LOAD)			
FREQ.(MHz)	10	100	1GHz
LIMITED (dB)	25	70	65
SCHEMATIC			
MARKING:			
PART: NONE			
BAG: SCI 1234-001			
DATE CODE			
LOT NO.			
QTY./BAG (200 MAX.)			

	8	7	6	5	4	3	2	1	0	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED
	CN #16035	CN 10418-CPD	CN 172443	CN 169615 REDRAWN	CN 156801	CN 155084	CN 150664	CN 148903	CN 146639	CHANGE NOTICE	Fractions ± 1/64
											Dec. .xx±
											Dec. .xxx± .010
											Angles ±0° 30'
											CODE IDENT. NO. OLSP2

		FAIRVIEW PENNSYLVANIA	
Dwn. D.Humphreys	Description		
Date 10-02-15	SURFACE MOUNT FILTER		
Engr. DEVINE	1234-001		
Scale NTS			