
KEMET Part Number: PME271M422MR30

(P276HE222M275A)



Capacitor, Film, Metallized Paper, 2200 pF, +/-20% Tol, -40/+110C, Safety: X2, 275 VAC, Lead Spacing=10.2 mm



General Information		
Supplier:	KEMET	
Dielectric:	Metallized Paper	
Application:	Safety: X2	
Style:	Radial Molded	
Lead Form:	Wire Leads	
Features:	Pulse	
Approvals:	ENEC,UL,cUL	
RoHS:	Yes	

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	13.5	MAX
Н	7.5	MAX
Т	3.9	MAX
S	10.2	+/-0.5
LL	30	+5
F	0.6	NOM

Specifications	
Capacitance:	2200 pF
Voltage:	630 VDC
Tolerance:	+/-20%
Voltage AC:	275 VAC
Rated Temperature:	110C
Temperature Range:	-40/+110C
Dissipation Factor @ 1 kHz:	1.3%
Insulation Resistance:	12 GOhm
Maximum dVdT:	1200 v/us
Miscellaneous:	SRF= 37 MHz

Packaging Specifications	
Package Kind:	Bulk
Package Quantity:	1000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

